

FEATURES & CAPABILITIES

ISU® 56000 Series



SYMBOLS



Certified for Helo-Lift Operations (where noted on each page)



Certifiable for Helo-Lift Operations (where noted on each page) - meaning internally certified by AAR, but official certification must come from U.S. Army Soldier Systems Center, Natick, MA, at the request of the user



Certified for Airlift Operations (roll-in and lock). No auxiliary equipment/tie-downs are required (where noted on each page)



Certifiable for Airlift Operations (where noted on each page) - meaning internally certified by AAR, but official certification must come at the request of the user

The following Features & Capabilities are applicable to all ISU® Containers (unless stated otherwise on individual product pages)

- Dimensions: 108" X 88" single-pallet standard base size, or 108" X 48" half-pallet base size, is 463L Certified - equipped to lock in aircraft cargo restraint system - no pallet required
- Four-way forkliftable with oversized forklift tubes; tube size 13 3/4" X 4.4"
- Intermodal - transportable by air, land, sea or rail
- Compatible with standard military transport vehicles/equipment 2.5-ton and 5-ton - FMTV, LMTV, HEMTT, Flatrack, CROP, etc.
- Base pre-drilled for optional caster set
- Ready for use with low or high-speed mobility wheel set
- All aluminum extruded, mechanically fastened pallet base certified not to damage aircraft roller systems
- 5,000 and 10,000 lb. payload capacities (depending on container and configuration)
- Weather, dust, and sand-proof
- Winching rings located at every lower corner
- Retractable folding steps for easy roof access for sling hookup
- Doors may be padlocked (user provides)
- Stackable two-high when loaded with up to 10,000 lbs. or empty (Note: KC Containers require adapter)
- Quickly removable centerpost between doors (without shelves installed) enables loading of large items
- Field service and depot level sustainment support available
- Specially designed shelves and trays (ordered separately) allow for the organization of parts, materials, or equipment within the ISU container
- All optional shelves are adjustable in one-inch vertical increments and are certified for 750 lbs. each
- Optional shelves are packed and shipped inside container for user's installation when requested as a kit. If required by individual contract, shelves can be installed at factory per specified spacing requirements, our field install can be arranged
- Easily integrated to meet any mission requirement

ISU® CONTAINER COLORS

Standard ISU® Container colors are green, tan or black; optional colors are grey, orange, or white (colors are designated by the third digit in the part number. Additional colors, including camo, may be requested through sales person (see Section 8 for sales contact information).

Standard Colors	GREEN	P/N 56100-000	FED-STD 34094
	TAN	P/N 56200-000	FED-STD 33446
	BLACK	P/N 56300-000	FED-STD 37030
Optional Colors	GREY	P/N 56400-000	FED-STD 36300
	ORANGE	P/N 56500-000	FED-STD 12197
	WHITE	P/N 56600-000	FED-STD 37875